

Width and Length Dimensions

► **Standard Rectangular**

Minimum Width: 8" Maximum Width: 108"
Minimum Length: 8" Maximum Length: 120"
* Standard hardware is color matched to the fabric.

► **Top Down - Bottom Up**

Minimum Width: 12" Maximum Width: 96"
Minimum Length: 12" Maximum Length: 96"
* Top Down - Bottom Up Shades are made with two operating cord locks, one on the left and one on the right side of shade. The right cord lowers the middle rail and left cord raises the bottom.

► **Continuous Cord Loop**

Minimum Width: 18" Maximum Width: 108"
Minimum Length: 8" Maximum Length: 120"
* A one-inch color coordinating strip is inserted into the white head rail to complement the fabric.
* Continuous cord loops are available 2' to 15' lengths in 1' intervals. Please specify length when ordering. Standard loop sizes are as follows:

Shade Length	Standard Loop
Up to and including 26 7/8"	1' (12")
27" to 39 7/8"	2' (24")
40" to 59 7/8"	3' (36")
60" to 83 7/8"	4' (48")
84" to 107 7/8"	5' (60")
108" and greater	6' (72")

► **Continuous Cord Loop Top Down - Bottom Up**

Minimum Width: 24" Maximum Width: 108"
Minimum Length: 8" Maximum Length: 120"
* Standard controls on Top Down - Bottom Up Shades: the right cord loop lowers the middle rail and left cord loop raises the bottom. Reverse controls are not available.

► **Cordless and Cordless Top Down - Bottom Up**

Minimum Width*: 18" ** Maximum Width: 96"
Minimum Length: 8" Maximum Length: 84"
* 18" OB or 18 7/8" IB
* A one-inch color coordinating strip is inserted into the white head rail to complement the fabric. The bottom and middle rail will coordinate with the fabric.

► **Motorization**

Minimum Width: 18" Maximum Width: 96"
Minimum Length: 8" Maximum Length: 120"
* A one-inch color coordinating strip is inserted into the white head rail to complement the fabric. The bottom rail will coordinate with the fabric.

► **Two-On-One Head Rail**

Minimum Width: 16" Maximum Width: 144"
Minimum Length: 8" Maximum Length: 120"
* Maximum width of any single panel is 108"
* 3/8" space between panels

► **Two-On-One Head Rail with Continuous Cord Loop**

Minimum Width: 36" Maximum Width: 144"
Minimum Length: 8" Maximum Length: 120"
* Minimum width of any single panel is 18"
* Maximum width of any single panel is 108"
* 3/8" space between panels

Mounting Specifications

► **Standard Rectangular**

* Minimum Shallow Mounting Surface: 3/4"
* Minimum Flush Inside Mounting Surface: 2 7/8"
* Minimum Outside Mounting Surface: 3/4"
* Minimum Side Mount Surface: 1 3/8"
* Minimum Flush Side Mount Surface: 1 7/8"

► **Continuous Cord Loop**

► **Continuous Cord Loop Top Down - Bottom Up**

► **Cordless and Cordless Top Down-Bottom Up**

► **Motorization**

* Minimum Shallow Mounting Surface: 1/2"
* Minimum Flush Inside Mounting Surface: 2 1/4"
* Minimum Outside Mounting Surface: 7/8"
* Minimum Side Mount Surface: 1 1/4"
* Minimum Flush Side Mount Surface: 2 1/4"