

# SIERRA™ 2" FAUXWOOD SPECIFICATIONS

- Minimum Width 8 3/4" - tilt only
- Maximum Width 96"
- Maximum Width Multiple blinds on one headrail - 120"
- Maximum Height 96"
- **Factory Allowances:**

| <b>Inside Mount</b>     | <b>Outside Mount</b>   |
|-------------------------|------------------------|
| Width - 1/2" (+/- 1/8") | Width - no deductions  |
| Length - no deductions  | Length - no deductions |
- Minimum depth requirement = 1"
- Minimum flush requirement (Crown valance) = 3 1/2"
- Lifetime limited warranty

## **Slats:**

Poly (expanded PVC) slat. Nominal 2" slat in width x 1/8" thick.

## **Headrail:**

2" x 2-1/4" U-shaped channel of .025-inch thick (before painted) iron phosphate treated steel. The channel is primed with baked acrylic and has a finish coat of polyester baked enamel in coordinating colors.

## **Bottomrail:**

Nominal 2" wide x 5/8" high. Finished to coordinate with slats.

## **Braided Ladders:**

Braided polyester yarn, 4 strands per rung with slat spacing of 44mm. Ladder spacing is 13 3/4" maximum between ladders and 4 1/2" maximum from each end.

## **Lift Cord:**

Braided polyester measuring 1.8mm in diameter with a minimum breaking strength of 175 pounds. Equipped with color coordinated poly tassels.

## **Tilt Rod Support:**

Low-friction thermoplastic provides support for tilt rod.

## **Tilter:**

Tilter is a worm and gear arrangement in an enclosed gear case (housing). Gear case of acetyl low-friction thermoplastic.

## **Cord Tilt (Standard):**

"Assisted lift" cord lock equipped with braided polyester cord and color-coordinated wood tassels.

## **Wand Tilt Optional:**

Color coordinated wood wands up to 48", Lucite wands over 48".

## **Cord Lock:**

All metal crash proof design with floating locking pin.

## **End Brackets:**

Treated steel with a vinyl primer and polyester baked enamel finish coat to match headrail. Rivet hinged front cover with safety lip.

## **Valance:**

Decorative Crown Valance is standard; made of expanded PVC, with clear plastic clips which attach to headrail. Returns are standard on all outside mounts.

## **Flammability:**

This product meets the flame resistant requirements established by National Fire Protection Agency Small Scale Test (NFPA701).

Vista Products, Inc.