


LEVOLOR®



Custom Roller Shades

Reference Guide

August 2026

For more info visit LEVOLOR.com

TABLE OF CONTENTS

Product Overview

- Collection Information (includes Opacity) 2-3
- Color Chart 4-6

Collection Specifications

- Spec Grid: Continuous Cord Loop / InMotion™ and Cordless 7-64
 - Screen Collections 7-21
 - Fabric Collections 22-64

Product Specifications

- Operating Systems: 65-66
 - Continuous Cord Loop 65
 - PerfectPlacement™ Cordless 66
- Top Treatment Cassettes 66
- Overview InMotion™ Wand 66
- Overview InMotion™ 67-68
- Top Treatment - Fabric Valance 69
- Privacy Side Channels 69
- Railroaded Material 70
- Bottomrail Options 70

Additional Options

- Roll Direction 71
- 2-on-1 71
- Magnetic Hold Down Bracket 71
- Cleaning and Care 71
- Product Characteristics & Information 72
- Mounting Requirements 73

Finished Dimensions

- Continuous Cord Loop and PerfectPlacement™ Cordless 74
- InMotion™ and InMotion™ Wand 75
- Solar Optical Chart and Information 76-79

Parts and Components

- Deluxe Valance 80
- Cordless Lift PerfectPlacement™ Open Roll 81
- Cordless Lift PerfectPlacement™ Cassette 82
- Continuous Loop Control 83-84
- InMotion™ Wand 85-86

The following information, listed below, is available online at LEVOLOR.com

- Terms and Conditions
- Freight
- Warning and Safety Information
- Order Processing
- Claims and Returns
- Warranty

COLLECTION INFORMATION

Collection Code	Collection Name	Roll Width	Composition	Opacity	Greenguard Certified	Railroad Option	Splice/Seam	Bottom Rail Omni Heat Sealed Aluminum	Panel Track
LS013	1% Catalina	118"	100% TPO -thermoplastic (PVC Free)	1% Openness	Yes	Yes	No	Omni Only	Yes
LS010	1% Newport	98"	25% Fiberglass, 75% PVC	1% Openness	Yes	Yes	Yes	All	Yes
LS049	1% Solapur	118"	70% PVC, 30% Polyester	1% Openness	Yes	Yes	Yes	All	Yes
LS008	3% Acadia	118"	18% Polyester, 25% Recycle Polyester, 57% PVC	3% Openness	Yes	No	No	All	Yes
LS026	3% Barcelona	113"	70% PVC, 30% Polyester	3% Openness	No	No	No	All	Yes
LS014	3% Catalina	118"	100% TPO -thermoplastic (PVC Free)	3% Openness	Yes	Yes	No	Omni Only	Yes
LS006	3% Malibu	118"	30% Polyester, 70%PVC	3% Openness	Yes	Yes	Yes	All	Yes
LS011	3% Newport	98"	25% Fiberglass, 75% PVC	3% Openness	Yes	Yes	Yes	All	Yes
LS027	3% Providence	113"	70% PVC, 30% Polyester	3% Openness	No	No	No	All	Yes
LS050	3% Revival	113"	30% Polyester, 70% PVC	3% Openness	No	No	No	All	Yes
LS028	3% Shangrila	113"	70% PVC, 30% Polyester	3% Openness	No	No	No	All	Yes
LS048	3% Solapur	118"	70% PVC, 30% Polyester	3% Openness	Yes	Yes	Yes	All	Yes
LS045	3% Stonewash	113"	30% Polyester, 70% PVC	3% Openness	No	No	No	All	Yes
LS009	5% Acadia	118"	18% Polyester, 25% Recycle Polyester, 57% PVC	5% Openness	Yes	No	No	All	Yes
LS015	5% Catalina	118"	100% TPO -thermoplastic (PVC Free)	5% Openness	Yes	Yes	No	Omni Only	Yes
LS005	5% Key West	118"	30% Polyester, 70%PVC	5% Openness	Yes	Yes	Yes	All	Yes
LS012	5% Newport	98"	25% Fiberglass, 75% PVC	5% Openness	Yes	Yes	Yes	All	Yes
LS047	5% Solapur	118"	70% PVC, 30% Polyester	5% Openness	Yes	Yes	Yes	All	Yes
LS007	5% Sonoma	118"	30% Polyester, 70%PVC	5% Openness	Yes	Yes	Yes	All	Yes
LS046	10% Solapur	118"	70% PVC, 30% Polyester	10% Openness	Yes	Yes	Yes	All	Yes
LF038	Aberdeen	110"	100% Polyester	Light Filtering	Yes	No	No	All	Yes
LF049	Aspen	110"	100% Polyester	Light Filtering	Yes	No	No	All	Yes
LB049	Aspen Blackout	110"	100% Polyester	Blackout	Yes	All	Yes	All	Yes
LF026	Barcelona	105"	100% Polyester	Light Filtering	No	No	No	All	Yes
LB026	Barcelona Blackout	105"	100% Polyester	Blackout	No	No	No	All	Yes
LF019	Bellamy	110"	100% Polyester	Light Filtering	No	No	No	All	Yes
LB019	Bellamy Blackout	110"	100% Polyester with Acrylic Coating	Blackout	No	No	No	All	Yes
LF054	Belmont	118"	90% Polyester, 10% Cationic Polyester	Semi-Sheer	Yes	No	No	All	Yes
LB054	Belmont Blackout	118"	90% Polyester, 10% Cationic Polyester	Blackout	Yes	No	No	All	Yes
LF052	Boulevard	110"	100% Polyester	Light Filtering	Yes	No	No	All	Yes
LB052	Boulevard Blackout	110"	100% Polyester	Blackout	Yes	No	No	All	Yes
LF033	Brighton	110"	100% Polyester	Light Filtering	No	No	No	All	Yes
LF046	Chelsea	118"	100% Polyester	Light Filtering	Yes	No	No	All	Yes
LB046	Chelsea Blackout	118"	100% Polyester	Blackout	Yes	No	No	All	Yes
LF055	Finnley	118"	100% Polyester	Light Filtering	No	No	No	Omni Only	Yes
LB055	Finnley Blackout	118"	100% Polyester	Blackout	No	No	No	All	Yes
LF050	Kashia	94"	100% Polyester	Light Filtering	No	No	No	All	Yes
LF018	Madison	110"	100% Polyester	Light Filtering	No	Yes	Yes	All	Yes
LB018	Madison Blackout	110"	100% Polyester with Acrylic Coating	Blackout	No	Yes	Yes	All	Yes
LB057	Midtown Blackout	110"	100% Polyester	Blackout	Yes	Yes	Yes	All	Yes
LF051	Monte Vista	94"	100% Polyester	Semi-Sheer	No	No	No	All	Yes
LB051	Monte Vista Blackout	94"	100% Polyester with Acrylic Coating	Blackout	No	No	No	All	Yes
LF056	Oxford	94"	100% Polyester	Light Filtering	No	No	No	All	Yes
LB056	Oxford Blackout	94"	100% Polyester	Blackout	No	No	No	All	Yes
LF027	Providence	113"	100% Polyester	Light Filtering	No	No	No	All	Yes
LB027	Providence Blackout	113"	100% Polyester	Blackout	No	No	No	All	Yes

NOTE: Refer to the specification charts on pages 7-64 for the minimum and maximum width and height of each fabric for specific system and/or top treatment. .

COLLECTION INFORMATION

Collection Code	Collection Name	Roll Width	Composition	Opacity	Greenguard Certified	Railroad Option	Splice/Seam	Bottom Rail Omni Heat Sealed Aluminum	Panel Track
LF039	Ravello	110"	100% Polyester	Light Filtering	Yes	Yes	Yes	All	Yes
LF047	Revival	105"	100% Polyester	Light Filtering	No	No	No	All	Yes
LB047	Revival Blackout	105"	100% Polyester	Blackout	No	No	No	All	Yes
LF028	Shangrila	113"	100% Polyester	Light Filtering	No	No	No	All	Yes
LB028	Shangrila Blackout	113"	100% Polyester	Blackout	No	No	No	All	Yes
LF045	Stonewash	105"	100% Polyester	Light Filtering	No	No	No	All	Yes
LB045	Stonewash Blackout	105"	100% Polyester	Blackout	No	No	No	All	Yes
LF048	Toulouse	110"	100% Polyester	Light Filtering	No	No	No	All	Yes
LB048	Toulouse Blackout	110"	100% Polyester with Acrylic Coating	Blackout	No	No	No	All	No
LF053	Valentina	122"	100% Polyester	Light Filtering	No	Yes	Yes	All	Yes
LB053	Valentina Blackout	120"	100% Polyester	Blackout	No	Yes	Yes	All	Yes
LF040	Valhalla	110"	93.3% Polyester, 6.7% Linen	Light Filtering	Yes	No	No	All	No
LB058	Vitality Blackout	72"	73% PVC, 27% Woven Fiberglass	Vinyl	Yes	Yes	Yes	All	Yes
LF035	Waverly	118"	100% Polyester	Light Filtering	No	No	No	All	Yes
LB035	Waverly Blackout	118"	100% Polyester	Blackout	No	No	No	All	Yes
LF020	Westport	118"	50% PES/50% ReOcPlastic	Semi-Sheer	Yes	No	No	All	Yes
LB020	Westport Blackout	114"	50% PES/50% ReOcPlastic	Blackout	Yes	No	No	All	Yes

NOTE: Refer to the specification charts on pages 7-64 for the minimum and maximum width and height of each fabric for specific system and/or top treatment. .

SCREEN COLOR CHART

Collection Code	Collection Name	Color Code	Screen Color	Component Set
LS013	1% Catalina	05	Onyx	Black
LS013	1% Catalina	04	Bronze	Bronze
LS013	1% Catalina	06	Carbon	Black
LS013	1% Catalina	02	Bone	Vanilla
LS013	1% Catalina	03	Nickel	Gray/Silver
LS013	1% Catalina	01	Powder	White
LS010	1% Newport	05	Onyx	Black
LS010	1% Newport	04	Bronze	Bronze
LS010	1% Newport	06	Carbon	Black
LS010	1% Newport	02	Bone	Vanilla
LS010	1% Newport	03	Nickel	Gray/Silver
LS010	1% Newport	01	Powder	White
LS049	1% Solapur	04	Bronze	Bronze
LS049	1% Solapur	03	Onyx	Black
LS049	1% Solapur	01	Powder	White
LS049	1% Solapur	06	Nickel	Gray/Silver
LS049	1% Solapur	05	Bone	Vanilla
LS046	10% Solapur	01	Powder	White
LS046	10% Solapur	03	Onyx	Black
LS046	10% Solapur	04	Bronze	Bronze
LS046	10% Solapur	05	Bone	Vanilla
LS046	10% Solapur	06	Nickel	Silver
LS008	3% Acadia	04	Onyx	Black
LS008	3% Acadia	05	Carbon	Black
LS008	3% Acadia	03	Nickel	Gray/Silver
LS008	3% Acadia	02	Bone	Vanilla
LS008	3% Acadia	01	Powder	White
LS026	3% Barcelona	02	Marine	White
LS026	3% Barcelona	01	Flintrock	Gray/Silver
LS014	3% Catalina	05	Onyx	Black
LS014	3% Catalina	04	Bronze	Bronze
LS014	3% Catalina	06	Carbon	Black
LS014	3% Catalina	02	Bone	Vanilla
LS014	3% Catalina	03	Nickel	Gray/Silver
LS014	3% Catalina	01	Powder	White
LS006	3% Malibu	04	Honeywheat	White
LS006	3% Malibu	01	Cinnamon	Bronze
LS006	3% Malibu	03	Cappuccino	Vanilla
LS006	3% Malibu	02	Beechwood	Gray/Silver
LS011	3% Newport	05	Onyx	Black
LS011	3% Newport	04	Bronze	Bronze
LS011	3% Newport	06	Carbon	Black
LS011	3% Newport	02	Bone	Vanilla
LS011	3% Newport	03	Nickel	Gray/Silver
LS011	3% Newport	01	Powder	White
LS027	3% Providence	02	Rose	White
LS027	3% Providence	05	Oyster	Vanilla
LS027	3% Providence	06	Julep	Gray/Silver
LS027	3% Providence	03	Fine Silver	Gray/Silver
LS027	3% Providence	04	Blue Jay	Gray/Silver
LS050	3% Revival	01	Static Noise	White
LS050	3% Revival	02	Paradise	White

Collection Code	Collection Name	Color Code	Screen Color	Component Set
LS050	3% Revival	03	Enchantment	White
LS028	3% Shangrila	02	Ginger Root	Vanilla
LS028	3% Shangrila	03	Eucalyptus	White
LS048	3% Solapur	04	Bronze	Bronze
LS048	3% Solapur	03	Onyx	Black
LS048	3% Solapur	01	Powder	White
LS048	3% Solapur	06	Nickel	Gray/Silver
LS048	3% Solapur	05	Bone	Vanilla
LS045	3% Stonewash	01	Fossil	Bronze
LS045	3% Stonewash	02	Denim	Silver
LS045	3% Stonewash	03	Ocean	Silver
LS009	5% Acadia	04	Onyx	Black
LS009	5% Acadia	05	Carbon	Black
LS009	5% Acadia	03	Nickel	Gray/Silver
LS009	5% Acadia	02	Bone	Vanilla
LS009	5% Acadia	01	Powder	White
LS015	5% Catalina	05	Onyx	Black
LS015	5% Catalina	04	Bronze	Bronze
LS015	5% Catalina	06	Carbon	Black
LS015	5% Catalina	02	Bone	Vanilla
LS015	5% Catalina	03	Nickel	Gray/Silver
LS015	5% Catalina	01	Powder	White
LS005	5% Key West	04	Oatmeal	White
LS005	5% Key West	02	Doe	Gray/Silver
LS005	5% Key West	01	Cocoa	Bronze
LS005	5% Key West	07	Iron Ore	Black
LS005	5% Key West	03	Mink	Gray/Silver
LS005	5% Key West	05	Burlap	Gray/Silver
LS005	5% Key West	06	Barley	Vanilla
LS012	5% Newport	05	Onyx	Black
LS012	5% Newport	04	Bronze	Bronze
LS012	5% Newport	06	Carbon	Black
LS012	5% Newport	02	Bone	Vanilla
LS012	5% Newport	03	Nickel	Gray/Silver
LS012	5% Newport	01	Powder	White
LS047	5% Solapur	04	Bronze	Bronze
LS047	5% Solapur	03	Onyx	Black
LS047	5% Solapur	01	Powder	White
LS047	5% Solapur	06	Nickel	Gray/Silver
LS047	5% Solapur	05	Bone	Vanilla
LS007	5% Sonoma	02	Ocean	Gray/Silver
LS007	5% Sonoma	01	Moss	Gray/Silver
LS007	5% Sonoma	10	Toast	Vanilla
LS007	5% Sonoma	03	Biscuit	Gray/Silver
LS007	5% Sonoma	05	Blush	White
LS007	5% Sonoma	09	Merlot	Black
LS007	5% Sonoma	07	Java	Black
LS007	5% Sonoma	06	Rosemary	Gray/Silver
LS007	5% Sonoma	04	Sea Glass	Gray/Silver
LS007	5% Sonoma	08	Pebble	Gray/Silver

Component Set includes plastic chain, chain tensioner, top treatments with end caps, open roll bracket covers, and bottom rail with end caps and are pre-selected based on screen/fabric color.

FABRIC COLOR CHART

Collection Code	Collection Name	Color Code	Fabric Color	Component Set
LF038	Aberdeen	04	Onyx	Black
LF038	Aberdeen	03	Shell	Gray/Silver
LF038	Aberdeen	02	Bone	White
LF038	Aberdeen	01	Pearl	White
LF049	Aspen	01	Heathered	Gray/Silver
LF049	Aspen	02	Champagne	Vanilla
LF049	Aspen	03	Laurel	White
LF049	Aspen	04	Winter White	White
LB049	Aspen Blackout	01	Heathered	Gray/Silver
LB049	Aspen Blackout	02	Champagne	Vanilla
LB049	Aspen Blackout	03	Laurel	White
LB049	Aspen Blackout	04	Winter White	White
LF026	Barcelona	02	Marine	White
LF026	Barcelona	01	Flintrock	Gray/Silver
LB026	Barcelona Blackout	02	Marine	White
LB026	Barcelona Blackout	01	Flintrock	Gray/Silver
LF019	Bellamy	03	Blue Steel	Gray/Silver
LF019	Bellamy	02	Carbonite	Black
LF019	Bellamy	04	Green Tea	Gray/Silver
LF019	Bellamy	01	Barley	Vanilla
LB019	Bellamy Blackout	03	Blue Steel	Gray/Silver
LB019	Bellamy Blackout	02	Carbonite	Black
LB019	Bellamy Blackout	04	Green Tea	Gray/Silver
LB019	Bellamy Blackout	01	Barley	Vanilla
LF054	Belmont	10	Whisper	White
LF054	Belmont	11	Champagne	White
LF054	Belmont	12	Dove	Black
LB054	Belmont Blackout	10	Whisper	White
LB054	Belmont Blackout	11	Champagne	White
LB054	Belmont Blackout	12	Dove	Black
LF052	Boulevard	06	Iron Ore	Black
LF052	Boulevard	01	Alabaster	Vanilla
LF052	Boulevard	02	Drift Wood	Gray/Silver
LF052	Boulevard	05	Coconut	White
LB052	Boulevard Blackout	06	Iron Ore	Black
LB052	Boulevard Blackout	01	Alabaster	Vanilla
LB052	Boulevard Blackout	02	Drift Wood	Gray/Silver
LB052	Boulevard Blackout	05	Coconut	White
LF033	Brighton	02	Toasted Almond	Vanilla
LF033	Brighton	04	Brushed Silver	Gray/Silver
LF033	Brighton	01	Shaved Coconut	White
LF033	Brighton	03	Weathered Bronze	Silver
LF046	Chelsea	01	Pearl Dust	White
LF046	Chelsea	02	Sandy Beige	Silver
LF046	Chelsea	03	Slate Gray	Black
LB046	Chelsea Blackout	01	Pearl Dust	White
LB046	Chelsea Blackout	02	Sandy Beige	Silver
LB046	Chelsea Blackout	03	Slate Gray	Black
LF055	Finnley	000	Whisper	White
LF055	Finnley	002	Light Gray	Silver
LF055	Finnley	003	Sand	Vanilla

Collection Code	Collection Name	Color Code	Fabric Color	Component Set
LB055	Finnley Blackout	000	Whisper	White
LB055	Finnley Blackout	001	Light Gray	Silver
LB055	Finnley Blackout	003	Sand	Vanilla
LF050	Kashia	201	Arabica Roast	Bronze
LF050	Kashia	202	Lentil Bean	Vanilla
LF018	Madison	01	Sea Oats	Silver
LF018	Madison	02	Biscuit	Vanilla
LF018	Madison	04	Denim	Gray/Silver
LF018	Madison	03	Nutmeg	Bronze
LB018	Madison Blackout	02	Biscuit	Vanilla
LB018	Madison Blackout	04	Denim	Gray/Silver
LB018	Madison Blackout	03	Nutmeg	Bronze
LB018	Madison Blackout	01	Sea Oats	Silver
LB057	Midtown Blackout	04	Oatmeal	Gray/Silver
LB057	Midtown Blackout	01	Ivory	White
LF051	Monte Vista	101	Stormy Night	Gray/Silver
LF051	Monte Vista	100	Driftwood	Gray/Silver
LF051	Monte Vista	106	Prairie Sky	Bronze
LF051	Monte Vista	107	Desert Horizon	Bronze
LB051	Monte Vista Blackout	02	Stormy Night	Gray/Silver
LB051	Monte Vista Blackout	01	Driftwood	Gray/Silver
LB051	Monte Vista Blackout	04	Prairie Sky	Bronze
LB051	Monte Vista Blackout	03	Desert Horizon	Bronze
LF056	Oxford	01	Powder	White
LF056	Oxford	02	Candlelight	White
LF056	Oxford	03	Mushroom	Vanilla
LF056	Oxford	04	Storm Cloud	Silver
LF056	Oxford	05	Charcoal	Black
LF056	Oxford	06	Taupe	Silver
LB056	Oxford Blackout	01	Powder	White
LB056	Oxford Blackout	02	Candlelight	White
LB056	Oxford Blackout	03	Mushroom	Vanilla
LB056	Oxford Blackout	04	Storm Cloud	Silver
LB056	Oxford Blackout	05	Charcoal	Black
LF027	Providence	01	Antique	White
LF027	Providence	02	Rose	White
LF027	Providence	05	Oyster	Vanilla
LF027	Providence	06	Julep	Gray/Silver
LF027	Providence	03	Fine Silver	Gray/Silver
LF027	Providence	04	Blue Jay	Gray/Silver
LB027	Providence Blackout	02	Rosse	White
LB027	Providence Blackout	05	Oyster	Vanilla
LB027	Providence Blackout	06	Julep	Gray/Silver
LB027	Providence Blackout	03	Fine Silver	Gray/Silver
LB027	Providence Blackout	04	Blue Jay	Gray/Silver
LF039	Ravello	01	Whisper	White
LF039	Ravello	03	Silver Mist	Gray/Silver
LF039	Ravello	02	Candlelight	White
LF047	Revival	01	Static Noise	White
LF047	Revival	02	Paradise	White
LF047	Revival	03	Enchantment	White

Component Set includes plastic chain, chain tensioner, top treatments with end caps, open roll bracket covers, and bottom rail with end caps and are pre-selected based on screen/fabric color.

FABRIC COLOR CHART

Collection Code	Collection Name	Color Code	Fabric Color	Component Set
LB047	Revival Blackout	01	Static Noise	White
LB047	Revival Blackout	02	Paradise	White
LB047	Revival Blackout	03	Enchantment	White
LF028	Shangrila	01	Wonton	White
LF028	Shangrila	02	Ginger Root	Vanilla
LF028	Shangrila	03	Eucalyptus	White
LB028	Shangrila Blackout	03	Eucalyptus	White
LB028	Shangrila Blackout	02	Ginger Root	Vanilla
LF045	Stonewash	01	Fossil	Bronze
LF045	Stonewash	02	Denim	Silver
LF045	Stonewash	03	Ocean	Silver
LB045	Stonewash Blackout	01	Fossil	Bronze
LB045	Stonewash Blackout	02	Denim	Silver
LB045	Stonewash Blackout	03	Ocean	Silver
LF048	Toulouse	06	Iron	Black
LF048	Toulouse	08	Nickel	Gray/Silver
LF048	Toulouse	07	Daylight	White
LF048	Toulouse	03	Dove	Gray/Silver
LF048	Toulouse	05	Charcoal	Gray/Silver
LF048	Toulouse	02	Blush	Vanilla
LF048	Toulouse	01	Snowfall	White
LB048	Toulouse Blackout	06	Iron	Black
LB048	Toulouse Blackout	08	Nickel	Gray/Silver
LB048	Toulouse Blackout	07	Daylight	White
LB048	Toulouse Blackout	03	Dove	Gray/Silver
LB048	Toulouse Blackout	05	Charcoal	Gray/Silver
LB048	Toulouse Blackout	02	Blush	Vanilla
LB048	Toulouse Blackout	01	Snowfall	White
LF053	Valentina	13	Nickel	Gray/Silver
LF053	Valentina	08	Toast	Gray/Silver
LF053	Valentina	11	Mist	Gray/Silver
LF053	Valentina	02	Oyster	White
LF053	Valentina	14	Skyline	Black
LF053	Valentina	17	Soft Gray	White
LF053	Valentina	12	Taupe	Gray/Silver
LF053	Valentina	03	Gray Sky	White
LF053	Valentina	05	Stone	Gray/Silver
LF053	Valentina	18	Khaki	Vanilla
LF053	Valentina	01	Cotton	White
LF053	Valentina	04	Mink	Bronze
LB053	Valentina Blackout	02	Oyster	White
LB053	Valentina Blackout	03	Toast	Vanilla
LB053	Valentina Blackout	06	Skyline	Gray/Silver
LB053	Valentina Blackout	09	Mist	Gray/Silver
LB053	Valentina Blackout	07	Nickel	Gray/Silver
LB053	Valentina Blackout	11	Soft Gray	White
LB053	Valentina Blackout	01	Cotton	White
LB053	Valentina Blackout	10	Gray Sky	White
LB053	Valentina Blackout	12	Khaki	Vanilla

Collection Code	Collection Name	Color Code	Fabric Color	Component Set
LB053	Valentina Blackout	04	Mink	Gray/Silver
LB053	Valentina Blackout	05	Taupe	Bronze
LB053	Valentina Blackout	08	Stone	Gray/Silver
LF040	Valhalla	03	Rye	Gray/Silver
LF040	Valhalla	02	Wheat	Vanilla
LF040	Valhalla	01	Oats	White
LB058	Vitality Blackout	11	Cream	Vanilla
LB058	Vitality Blackout	05	Warm White	Vanilla
LB058	Vitality Blackout	01	White	White
LF035	Waverly	01	Bone	White
LF035	Waverly	02	Linen	Vanilla
LF035	Waverly	04	Smoke	Black
LF035	Waverly	03	Dove	Bronze
LB035	Waverly Blackout	01	Bone	White
LB035	Waverly Blackout	02	Linen	Vanilla
LB035	Waverly Blackout	04	Smoke	Black
LB035	Waverly Blackout	03	Dove	Bronze
LF020	Westport	06	Pepper	Black
LF020	Westport	05	Key Lime	Gray/Silver
LF020	Westport	03	Silverdrop	Vanilla
LF020	Westport	04	Amethyst	Gray/Silver
LF020	Westport	02	Silverleaf	Gray/Silver
LF020	Westport	01	Cotton	White
LB020	Westport Blackout	06	Pepper	Black
LB020	Westport Blackout	03	Silverdrop	Vanilla
LB020	Westport Blackout	02	Silverleaf	Gray/Silver
LB020	Westport Blackout	01	Cotton	White


Component Set includes plastic chain, chain tensioner, top treatments with end caps, open roll bracket covers, and bottom rail with end caps and are pre-selected based on screen/fabric color.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS013	1% Catalina	118"	132"	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS013	1% Catalina	108"	108"	Yes

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS010	1% Newport	98"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS010	1% Newport	96"	96"	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS049	1% Solapur	118"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS049	1% Solapur	102"	102"	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS008	3% Acadia	118"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS008	3% Acadia	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS014	3% Catalina	118"	132"	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS014	3% Catalina	108"	108"	Yes

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS006	3% Malibu	118"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS006	3% Malibu	102"	102"	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS011	3% Newport	98"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS011	3% Newport	98"	102"	Yes

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS026	3% Barcelona	113"	N/A	No
LS027	3% Providence	113"	N/A	No
LS050	3% Revival	113"	N/A	No
LS028	3% Shangrila	113"	N/A	No
LS048	3% Solapur	118"	132"	Yes
LS045	3% Stonewash	113"	N/A	No

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS026	3% Barcelona	102"	N/A	No
LS027	3% Providence	102"	N/A	No
LS050	3% Revival	102"	102"	No
LS028	3% Shangrila	102"	N/A	No
LS048	3% Solapur	102"	102"	No
LS045	3% Stonewash	102"	102"	No

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS009	5% Acadia	118"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS009	5% Acadia	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS015	5% Catalina	118"	132"	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS015	5% Catalina	108"	108"	Yes

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS005	5% Key West	118"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS005	5% Key West	102"	102"	Yes

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS012	5% Newport	98"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS012	5% Newport	98"	102"	Yes

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS047	5% Solapur	118"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS047	5% Solapur	102"	102"	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS007	5% Sonoma	118"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS007	5% Sonoma	102"	102"	Yes

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All

No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS046	10% Solapur	118"	132"	Yes


- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".

- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.

- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"

- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			



Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B


No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS046	10% Solapur	102"	102"	Yes

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"

Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF038	Aberdeen	110"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF038	Aberdeen	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF049	Aspen	110"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF049	Aspen	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB049	Aspen Blackout	110"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB049	Aspen Blackout	102"	102"	Yes

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LS026	Barcelona	105"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF026	Barcelona	105"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB026	Barcelona Blackout	105"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB026	Barcelona Blackout	102"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF019	Bellamy	110"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF019	Bellamy	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All

No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB019	Bellamy Blackout	110"	N/A	No


- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".

- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.

- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"

- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			



Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B


No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB019	Bellamy Blackout	102"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"

Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF054	Belmont	118"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF054	Belmont	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All

No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB054	Belmont Blackout	118"	N/A	No


- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".

- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.

- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"

- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			



Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B


No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB054	Belmont Blackout	102"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"

Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF052	Boulevard	110"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF052	Boulevard	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All

No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB052	Boulevard Blackout	110"	N/A	No


- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".

- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.

- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"

- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			



Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B


No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB052	Boulevard Blackout	102"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"

Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF033	Brighton	110"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF033	Brighton	108"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF046	Chelsea	118"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF046	Chelsea	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB046	Chelsea Blackout	118"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB046	Chelsea Blackout	102"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF055	Finnley	118"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF055	Finnley	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB055	Finnley Blackout	118"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB055	Finnley Blackout	102"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF050	Kashia	94"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF050	Kashia	94"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All

No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF018	Madison	110"	132"	Yes


- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".

- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.

- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"

- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			



Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B


No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF018	Madison	102"	102"	Yes

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"

Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB018	Madison Blackout	110"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB018	Madison Blackout	102"	102"	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB057	Midtown Blackout	110"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB057	Midtown Blackout	102"	102"	Yes

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All

No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF051	Monte Vista	94"	N/A	No


- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".

- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.

- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"

- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			



Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B


No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF051	Monte Vista	94"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"

Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All

No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB051	Monte Vista Blackout	94"	N/A	No


- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".

- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.

- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"

- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			



Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B


No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB051	Monte Vista Blackout	94"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"

Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB056	Oxford Blackout	118"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB056	Oxford Blackout	94"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF027	Providence	113"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF027	Providence	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB027	Providence Blackout	113"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB027	Providence Blackout	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF039	Ravello	110"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF039	Ravello	108"	108"	Yes

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF047	Revival	105"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF047	Revival	108"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB047	Revival Blackout	105"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB047	Revival Blackout	102"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF028	Shangrila	113"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only; Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF028	Shangrila	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only; Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB028	Shangrila Blackout	113"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB028	Shangrila Blackout	108"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF045	Stonewash	105"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF045	Stonewash	105"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB045	Stonewash Blackout	105"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB045	Stonewash Blackout	102"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF048	Toulouse	110"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF048	Toulouse	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB048	Toulouse Blackout	110"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB048	Toulouse Blackout	102"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF053	Valentina	122"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF053	Valentina	108"	108"	Yes

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB053	Valentina Blackout	120"	132"	Yes

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB053	Valentina Blackout	108"	108"	Yes

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF040	Valhalla	110"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF040	Valhalla	108	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All

No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB058	Vitality Blackout	72"	132"	Yes


- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".

- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.

- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"

- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			



Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B


No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB058	Vitality Blackout	72"	102"	Yes

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"

Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF035	Waverly	118"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF035	Waverly	108"	N/A	No

- *Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB035	Waverly Blackout	118"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB035	Waverly Blackout	108"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All


No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF020	Westport	118"	N/A	No

- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".
- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.
- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"
- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			




Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B

No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12". Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LF020	Westport	108"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"
Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All

No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

PRODUCT SIZE SPECIFICATIONS

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB020	Westport Blackout	114"	N/A	No


- Railroad Fabrics (turned width for length) will have a visible seam when fabricated longer than the maximum roll width less 16".

- **Red Box** in spec chart indicates shade sizes Heat Sealed Hem Bar for these sizes.

- Maximum width of continuous Fabric Valance = Maximum published non-railroaded width less 8"

- Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
Fabric Valance			
Open Roll			



Control Systems (Minimum height for all Control Systems is 12")	Minimum Width (Single Panel)	Minimum Height	Overall Minimum Width (2-on-1)	Specification Zone(s)
Continuous Cord Loop (Maximum height for 12" width is 60")	12"	12"	24"	A, B & C
InMotion™ Wand	21"	12"	43"	A & B
InMotion™	21 1/2"	12"	44"	A & B


No-Drill Headrail available on InMotion™ with Medium Cassette only: Minimum Width for InMotion Wand is 22 1/2" and for InMotion Minimum Width is 22". Minimum height for both is 12".
Not available at all Retailers.

Collection Code	Collection Name	Max Width Non-Railroaded	Max Width Railroaded	Available with Seam
LB020	Westport Blackout	102"	N/A	No

*Maximum width of continuous Deluxe Valance = Maximum published non-railroaded width less 8"

Maximum Width and Height for No-Drill Headrail is 84". Not available at all Retailers.

Top Treatment	Legend		
Medium Cassette			
Large Cassette			
*Fabric Valance			
Open Roll with Mounting Bar			



Control Systems	Minimum Width (Single Panel)	Overall Minimum Width (2 on 1)	Minimum Height	Top Treatment
PerfectPlacement™ - Cordless	18"	N/A	24"	All

No-Drill Headrail available on PerfectPlacement™ Cordless with Medium Cassette only: Minimum Width is 18 1/2". Minimum height is 24". Not available at all Retailers.

OPERATING SYSTEM: CONTINUOUS CORD LOOP

Continuous Cord Loop

This operating system features a continuous bead chain loop with tensioner. As the clutch with attached chain is pulled up and down, it rotates the roller tube, enabling the roller shade to be lowered and raised. Bead stops are included to set at upper and lower shade limits.

- Universal brackets – color coordinated to clutch (Black or White)



Defaulted Chain Loop Length

Shade Height	Loop Drop
**12" to 15 7/8"	2/3 of Shade Height
**16" to 31 7/8"	2/3 of Shade Height
32" to 37 7/8"	24" loop
38" to 43 7/8"	30" loop
44" to 52 7/8"	36" loop
53" to 61 7/8"	42" loop
62" to 70 7/8"	48" loop
71" to 79 7/8"	54" loop
80" to 88 7/8"	60" loop
89" to 96 7/8"	66" loop
97" to 105 7/8"	72" loop
106" to 123 7/8"	84" loop
124" to 144"	96" loop

**Sizes require metal chain

Tensioner will color coordinate with fabric color.
(Changing the tensioner color is not an available option.)

Plastic bead chains are available in the following colors:

- Black • Bronze • Vanilla • White • Gray

Stainless Steel chain is available at no additional charge

NOTE: Stainless steel chain is recommended for all shades over 108" x 90". To avoid heavy pull force with the Continuous Cord Loop shade, InMotion™ is a great options with a minimal surcharge.



OPERATING SYSTEMS: PERFECTPLACEMENT™ CORDLESS

PerfectPlacement™ Cordless

- Effortless positioning of the shade by simply raising & lowering the shade to the desired position.
- Maximum Size: 108" x 120" (varies by fabric)
- Minimum Size: 18" x 24"
- Available with
 - o All fabric & screen collections and top treatments
 - o Standard or reversed roll (Reversed roll is not available with curved cassette)
 - o Single shade (not available 2-on-1 or 3-on-1)
 - o Omni Curved Wrapped, Bottom Rail
 - o Handles are enclosed to help keep fabric-wrapped bottomrail clean. 2 handles will be provided for shades wider than 42"
 - o Extension pole is available to use with handles on curved Omni Bottom rail when shades are hard to reach. Surcharge applies.



TOP TREATMENT – CASSETTES

Curved Cassette

- Sizes: Medium (3-1/8" height x 3-3/4" depth)
Large (3-7/8" height x 3-7/8" depth)
- Available in Matte Colors – White, Vanilla, Silver, Bronze, Black
- Features a fabric insert in the same fabric used for the shade.
Insert fabric will run the same direction as the fabric of the shade.
- Available with all operating systems except for AC motors
- No Reverse Roll



OVERVIEW INMOTION™ WAND

OPTIONS:

Wand colors: White, Vanilla, Gray, Bronze, Black. (Preselected based on fabric color)

Wand lengths: 1 ft (12"), 2 ft (24"), 3 ft (36"), 4 ft (48"), 5 ft (60), 6 ft (72")

Can be ordered for right or left side placement


One plug-in charger is required for each order



Motorization Overview

LEVOLOR® INMOTION™

Experience motorization like never before with smart home integration and automated scheduling. Take full control of your shades using voice command, the intuitive app, or remote.



Standard Remote
Requires 2 x AAA batteries, included.



Hub
Requires 5V 2A adapter, included. Connect up to 30 shades per hub.



App
Phone sold separately

App Requirements:
- LEVOLOR Hub
- 2.4 GHz Wi-Fi Network
- Apple® iOS10.0 or newer
- Android™4.1 or newer

Works With:
- Amazon Alexa
- Google Home
- IFTT
- Samsung SmartThings
- Siri

- Upgrade to motorization to control shades with remote or app.
- Powered by an integrated, rechargeable lithium-ion battery.
- Recharge with included magnetic micro-USB charger.
- Control shades with the 15-channel remote (sold separately).
- Add the hub (sold separately) to sync with your Wi-Fi to enable app control and smart home integration.
- Organize shades by room.
- See real-time shade position and battery charge status.
- Store preset shade positions as scenes.
- Create routines by scheduling scenes by day of week and time of day, even proximity to sunrise or sunset.
- Adjust shades when you are away from home.
- App available to download for iOS and Android devices.

Visit LEVOLOR.com/InMotion for additional information.

NOTE: LEVOLOR® InMotion™ is not compatible with products from the previous LEVOLOR® motorization program. This includes blinds/shades that are controlled with the previous LEVOLOR app, 3-channel remote, and 6-channel remote.

For additional information visit LEVOLOR.com

InMotion™ Accessories Overview

LEVOLOR® INMOTION™ WALL SWITCH

The InMotion™ Wall Remote lets you achieve effortless light control with the touch of a button, mounted to a wall to avoid misplacement. A great solution for hard to reach windows or in grand rooms with various automated solutions.

- Integrates with the LEVOLOR InMotion™ App or simply works by itself
- Operates an unlimited number of LEVOLOR motorized window coverings
- Features a clean, modern design with easy to use controls
- Activate group control and favorite position with a touch of a button
- Control up to 15-channels from one remote
- Hide unused channels for faster channel selection and scrolling
- Locking feature to prevent accidental programming changes
- No need to cut in to wall with the wireless design
- Dimensions: 3.4" L x 3.4" W x 0.7" D



LEVOLOR® INMOTION™ SOLAR PANEL

Harness the power of solar energy to power your motorized blinds and shades, ensuring reliable and efficient performance. A great choice for hard to reach windows.

- One Solar Panel per shade or blind is needed
- Easy to install and the low profile design is easy to conceal
- Provides a continuous charge to internal rechargeable batteries
- Syncs with the LEVOLOR InMotion™ App to show battery level
- Not recommended on north facing windows
- Micro USB charging cable, 59" long (included)
- Can be added to any existing InMotion™ blind or shade
- Dimensions: 18.7" L x 2" W x .30" D



FABRIC VALANCE

- Available with Roller Shade or as a stand alone cornice.
- Has clear edge groovers to hold the coordinating fabric in place.
- Standard height 3-5/8"
- Direction of fabric insert follows shade installed below.
- If valance is wider than material width, and shade below is not railroaded; valance fabric insert will be made with a center seamed like image shown below.



- Default return length:
 - Inside Mount: No returns
 - Outside Mount: 6-5/8" (overall 7-3/8")

Note: When ordering returns, valance corner cap adds 3/4" to the valance return depth.



PRIVACY SIDE CHANNELS

Privacy Side Channels

- Available in 5 colors: White, Gray, Vanilla, Bronze and Black
- Inside Mount Only
- High quality PVC light block installs in minutes
- Option offers additional privacy and room darkening
- Available with Cordless, InMotion™ Wand and InMotion™ operating systems
- If Privacy Side Channels are selected, a 1/2" will be deducted in addition to the 1/4" for inside mount



Surcharge applies.

RAILROADED MATERIAL

Railroaded Material

Railroaded material is when the fabric is turned on its side; using the material roll length for the shade width to increase the maximum width when available. Depending on the weaves/construction, many of the fabric collections can be railroaded but with visible seam when the shade is extended. Fabrics that are railroaded may curl along the edge.

When a shade needs to be railroaded, it is highly recommended to railroad all other shades within the same room for a uniform look.

Seams may be visible when the shade is fully extended. Seams will be placed as close to the tube as possible, location may varied depending upon roll width and shade height.

Although we maintain the highest quality standards, an exact pattern match at the seam on individual shades cannot be guaranteed. Pattern matches from shade to shade, horizontally or vertically, on multiple shade orders cannot be guaranteed.



BOTTOMRAIL OPTIONS



Omni Curved
(Wrapped)

Heat Sealed

Heat Sealed Aluminum (1-1/4")

The aluminum bar is inserted and heat sealed into the hem pocket. Heat Seal Hem bar is highly recommended on bigger and wider shades made with railroaded or heavier material to improve appearance of the shades. The hem bar helps reduce waviness, twisting, cupping & curling.

Not available on all styles. Please refer to the Collection Information section on pages 2-3.


Omni Bottom Rail (~1-1/8")

Available in White, Vanilla, Bronze, Black, and Silver matte finishes. Only front face of rail is wrapped.

Bottomrail End Caps are color coordinated to the bottomrail. Changing color of the end cap is not an option.



Heat sealed hem to back
pocket edges come sealed





Heat sealed hem bar is highly recommended when shade is ordered with railroaded material or when shade is equal, wider than 108" or longer than 90".

ADDITIONAL OPTIONS

ROLL DIRECTION

When ordering, please be sure to specify **ROLL DIRECTION**

- Extended Projection Bracket
(not available with Curved Cassette)




2-ON-1 OPTIONS – SPECIFY ON ORDER

- A two-on-one shade is two individual shades housed under one continuous top treatment.
- Top Treatment: Medium/Large Curved Cassette.
- Operating System: Continuous Cord Loop, InMotion™ Wand and InMotion™.
- Control Position: Left for left panel and right for right panel.
- Middle gap between the 2 shades is 1/2". Please refer to the Product Size Specifications for individual shade sizes and Feature & Options for option availability.
 - Tolerance: Height ≤ 60 ", $+1/4$ "; Height ≤ 120 ", $+3/8$ "; Height > 120 ", $+1/2$ "
- Price as 2 separate shades added together.
- Heat sealed hem bottom rail is strongly recommended to improve the appearance of the shade. It will help minimize waviness, twisting, cupping, and curling, especially on shade greater than 108" x 90".

NOTE: There is a 1/2" Continuous Cord Loop Control between the two shades. Please refer to the Product Size Specifications for individual shade sizes and Features and Options for option availability.

MAGNETIC HOLD DOWN BRACKET

- Available for all control systems
- Available with all bottom rail options
- Outside Mount Only
- Shade will ship with magnets attached onto the bottom rail
- Not available for reverse roll
- Magnet and Catch are Silver Color



CLEANING AND CARE INFORMATION

- Periodic vacuum using an upholstery attachment when shade is dusty. Dust also can gently remove with a dusting cloth.
- Do not immerse the shade in the water. Shade may be gently clean with a damp cloth. After cleaning, keep the shade lowered to allow the shade to dry completely before raising the shade.
- Loose fibers may appear on material edges from time to time. This is normal and does not affect the overall integrity of the shade. Simply trim off the loose fibers with a pair of sharp scissors.

PRODUCT CHARACTERISTICS & INFORMATION

Fabric & Shade Recommendations

- To ensure color consistency and minimize dye lot variation, order all shades for the same room at the same time.
- When a shade needs to be railroaded, railroad all other shades within the same room for uniform look.
- Heat sealed hem bar is highly recommended with large shades for best shade appearance.
- Heavy shades may require some assistance to lift. PerfectPlacement™ Cordless, and InMotion™ Wand are an affordable way to replace Continuous Cord Loop and transition to a contemporary look.
- Shade over 144" in width requires motorized shade.

Large Roller Shades Solutions

Most fabrics can be railroaded as an option for wider roller shades. Railroad is when material is turned 90° clockwise (using the roll length for the shade width). LEVOLOR® has performed extensive testing on all fabrics at various width to ensure customers are provided with high quality shades. However, there may be some visual differences when fabric is railroaded for shades wider than 90". These differences are consider normal characteristics.

- Fabrics may curl along the edge or have slight overall waviness
- A slight V may appear in the center of the shade due to the weight of the fabric
- Tube deflection

As the above characteristics are normal and expected with very wide shades, requests for remakes and/or credits will not be considered. We suggest reducing the shade width by splitting the one wide shade to two or more individual shades.



MOUNTING REQUIREMENTS

INSIDE MOUNT (IM)	Minimum Mounting Depth	Flush Mounting Depth
No Top Treatment	1-3/8"	2-1/8" to 4" (depending on roll diameter)
PerfectPlacement™ Cordless Lift	1-3/8"	2-1/8" to 4" (depending on roll diameter)
Medium Curved Cassette	1-1/2"	3-3/4"
Large Curved Cassette	1-1/2"	4-3/8"
Fabric Valance (with returns)	1-7/8"	4-1/4"
Fabric Valance (without returns)	1-1/4"	3-1/8"
Medium Curved Cassette with No-Drill Headrail	N/A	2-1/4"

NOTE: No-Drill Headrail not available at all Retailers.

OUTSIDE MOUNT (OM)	Minimum Mounting Surface Height
Continuous Cord Loop	1-5/8"
PerfectPlacement™ Cordless Lift	1-5/8"
Medium Curved Cassette	3-1/8"
Large Curved Cassette	4"
Fabric Valance	2"

TWO ON ONE SHADE SIZE STANDARDS	
Minimum ordered width - Cassette Valance	16"
Maximum ordered width - Cassette Valance	144"
Maximum Height	See Spec Chart
Center Gap	*1/2"

*Not available for PerfectPlacement™ Cordless Lift

TOP TREATMENT ONLY

FABRIC VALANCE (ONLY)	INSIDE MOUNT (IM)	OUTSIDE MOUNT (OM)
Valance Width Tip to Tip (no returns)	3/16 less than ordered width	N/A
Valance Width Tip to Tip (with returns)	N/A	1-3/8 greater than ordered width

FINISHED DIMENSIONS

Adjustments are taken from ordered dimensions. Width and height may vary $\pm 1/8"$

Continuous Cord Loop Shades

For all options, Shade Height = Ordered Height

		Inside Mount (IM)	Outside Mount (OM)
Open Roll (No Top Treatment)	Shade Width	3/16" less than ordered width	Ordered Width
	Fabric & Tube Width (no end caps)	1-3/16" less than ordered width	N/A
	Fabric & Tube Width (with end caps)	1-5/16" less than ordered width	1-1/8" less than ordered width
	<i>Control Side (in)</i>	11/16"	9/16"
	<i>Idler Side (in)</i>	1/2"	7/16"

Fabric Valance	Valance Width (no returns)	3/16" less than ordered width	Ordered Width
	Valance Width (with returns)	1-3/8" greater than ordered width	1-3/8" greater than ordered width
	Fabric & Tube Width	1-3/16" less than ordered width	1-1/8" less than ordered width
	<i>Control Side (in) - Skyline</i>	11/16"	9/16"
	<i>Idler Side (in) - Skyline</i>	1/2"	7/16"

Medium/Large Curved Cassette	Cassette Width	3/16" less than ordered width	Ordered Width
	Fabric & Tube Width	1-5/16" less than ordered width	1-1/8" less than ordered width
	<i>Control Side (in)</i>	13/16"	11/16"
	<i>Idler Side (in)</i>	1/2"	7/16"

PERFECTPLACEMENT™ CORDLESS LIFT

For all options, Shade Height = Ordered Height

		Inside Mount (IM)	Outside Mount (OM)
Open Roll (No Top Treatment)	Shade Width (with end caps)	1/8" less than order width	Ordered width
	Fabric/Tube Width (with end caps)	1 1/2" less than order width	1-3/8" less than ordered width
	<i>Control Side (in)</i>	13/16"	3/4"
	<i>Idler Side (in)</i>	11/16"	5/8"

Fabric Valance	Valance Width (no returns)	3/16" less than ordered width	Ordered width
	Valance Width (with returns)	1-3/8" greater than ordered width	1-3/8" greater than ordered width
	Fabric/Tube Width	1-1/2" less than order width	1-3/8" less than ordered width
	<i>Control Side (in)</i>	13/16"	3/4"
	<i>Idler Side (in)</i>	11/16"	5/8"

Medium/Large Curved Cassette	Cassette Width	3/16" less than ordered width	Ordered width
	Fabric/Tube Width	1-15/16" less than ordered width	1-1/8" less than ordered width
	<i>Control Side (in)</i>	7/8"	3/4"
	<i>Idler Side (in)</i>	1/2"	7/16"

- Fabric width + 1/4" to determine width of bottom rail with end caps. For shade with heat sealed hem bar, bottom rail width equates to fabric width.
- Shade width for open roll is measured from bracket end to bracket end (valance width measured separately).
- For shades with cassette, shade width is measured from cassette end cap to top treatment end cap.

FINISHED DIMENSIONS

Adjustments are taken from ordered dimensions. Width and height may vary $\pm 1/8"$

INMOTION™ MOTORIZATION

For all options, Shade Height = Ordered Height

	Inside Mount (IM)		Outside Mount (OM)
	Shade Width	3/16" less than ordered width	Ordered Width
	Fabric & Tube Width (no end caps)	1-1/4" less than ordered width	1-1/16" less than ordered width
	Fabric & Tube Width (with end caps)	1-3/8" less than ordered width	1-3/16" less than ordered width
	Control Side (in)	13/16"	11/16"
	Idler Side (in)	7/16"	3/8"

Fabric Valance	Valance Width (no returns)	3/16" less than ordered width	Ordered Width
	Valance Width (with returns)	1-3/8" greater than ordered width	1-3/8" greater than ordered width
	Fabric & Tube Width	1-1/4" less than ordered width	1-3/16" less than ordered width
	Control Side (in)	13/16"	3/4"
	Idler Side (in)	7/16"	7/16"

Medium/Large Curved Cassette	Cassette Width	3/16" less than ordered width	Ordered Width
	Fabric & Tube Width (with end caps)	1-1/2" less than ordered width	1-5/16" less than ordered width
	Control Side (in)	7/8"	3/4"
	Idler Side (in)	5/8"	9/16"

INMOTION™ WAND

For all options, Shade Height = Ordered Height

	Inside Mount (IM)		Outside Mount (OM)
	Shade Width	3/16" less than ordered width	Ordered Width
	Fabric & Tube Width (no end caps)	1-3/16" less than ordered width	1" less than ordered width
	Fabric & Tube Width (with end caps)	1-5/16" less than ordered width	1-1/8" less than ordered width
	Control Side (in)	13/16"	11/16"
	Idler Side (in)	3/8"	5/16"

Fabric Valance	Valance Width (no returns)	3/16" less than ordered width	Ordered Width
	Valance Width (with returns)	1-3/8" greater than ordered width	1-3/8" greater than ordered width
	Fabric & Tube Width	1-3/16" less than ordered width	1-1/8" less than ordered width
	Control Side (in)	13/16"	3/4"
	Idler Side (in)	3/8"	3/8"

Medium/Large Curved Cassette	Cassette Width	3/16" less than ordered width	Ordered Width
	Fabric & Tube Width (with end caps)	1-7/16" less than ordered width	1-1/4" less than ordered width
	Control Side (in)	7/8"	3/4"
	Idler Side (in)	9/16"	1/2"

- Fabric width + 1/4" to determine width of bottom rail with end caps. For shade with heat sealed hem bar, bottom rail width equates to fabric width.
- Shade width for open roll is measured from bracket end to bracket end (valance width measured separately).
- For shades with cassette, shade width is measured from cassette end cap to top treatment end cap.

SOLAR OPTICAL INFORMATION

The following pages contain solar optical information by pattern and color, it is important to understand the numbers and how they work best to your need.

OPENNESS FACTOR (OF):

OF is a property that is often used to describe a screen material. The definition of OF is the percentage of the screen's surface area that is "open". The OF only describes one of the factors that regulates the amount of light passing through a roller shade.

The OF and color coating together will decide how open the (shade) material will become. Different material colors absorb light differently. For example, a dark colored car is hotter than a light colored car.

Sunlight that hits the shade surface is divided into three parts that together make 100 % of the incoming light. The picture below illustrates the phenomenon.


TRANSMISSION: One part of the light will pass through the shade, and that is the part of the light that comes into the room. *The lower the number, the better.*

The transmission value tells how much light passes through the fabric. The transmission is dependent on three factors;

- the openness factor of the fabric
- the color of the fabric
- the coating on the fabric.

REFLECTION: One part of the light will be reflected when it hits the shade. *The higher the number, the better.*

ABSORPTION: The rest of the light will be absorbed by the shade. *The lower the number, the better.*



UV PROTECTION (and Blackout Fabrics): The total solar incident radiation of wavelengths between 280 nm and 2500 nm is measured and optical values are reported. UV-light is included in these wavelengths. For those of our fabrics that are Blackout the transmission of light is 0 %. This signifies 100 % blocking of all sunlight, including UV-light. The UV-protection is 100 % for the fabric. In order to get complete blocking of the light the fabric has to be fitted so that no light is transmitted on the sides of the fabric. *The higher the number, the better.*

SOLAR OPTICAL CHART

Collection Code	Collection Name	Color	Color Name	Openness	Transmission*	Reflection*	Absorption*	UV Rating
LS013	1% Catalina	01	Powder	1%	20	65	15	99%
LS013	1% Catalina	02	Bone	1%	18	55	27	99%
LS013	1% Catalina	03	Nickel	1%	14	50	36	99%
LS013	1% Catalina	04	Bronze	1%	1	4	95	99%
LS013	1% Catalina	05	Onyx	1%	1	3	96	99%
LS013	1% Catalina	06	Carbon	1%	4	14	82	99%
LS010	1% Newport	01	Powder	1%	10	65	25	99%
LS010	1% Newport	02	Bone	1%	15	58	27	99%
LS010	1% Newport	03	Nickel	1%	10	48	42	99%
LS010	1% Newport	04	Bronze	1%	1	5	94	99%
LS010	1% Newport	05	Onyx	1%	1	4	95	99%
LS010	1% Newport	06	Carbon	1%	4	10	86	99%
LS049	1% Solapur	01	Powder	1%	26	66	8	99%
LS049	1% Solapur	03	Onyx	1%	0	3	96	99%
LS049	1% Solapur	04	Bronze	1%	0	5	95	99%
LS049	1% Solapur	05	Bone	1%	12	73	15	99%
LS049	1% Solapur	06	Nickel	1%	5	58	37	99%
LS008	3% Acadia	01	Powder	3%	25	65	10	97%
LS008	3% Acadia	02	Bone	3%	25	53	22	97%
LS008	3% Acadia	03	Nickel	3%	16	40	44	97%
LS008	3% Acadia	04	Onyx	3%	5	6	89	97%
LS008	3% Acadia	05	Carbon	3%	7	21	72	97%
LS026	3% Barcelona	01	Westport Gray	3%	N/A	N/A	N/A	97%
LS026	3% Barcelona	02	Royal Navy	3%	N/A	N/A	N/A	97%
LS014	3% Catalina	01	Powder	3%	23	64	13	97%
LS014	3% Catalina	02	Bone	3%	17	51	32	97%
LS014	3% Catalina	03	Nickel	3%	15	44	41	97%
LS014	3% Catalina	04	Bronze	3%	4	5	91	97%
LS014	3% Catalina	05	Onyx	3%	4	5	91	97%
LS014	3% Catalina	06	Carbon	3%	4	13	83	97%
LS006	3% Malibu	01	Cinnamon	3%	6	22	72	97%
LS006	3% Malibu	02	Beechwood	3%	7	37	56	97%
LS006	3% Malibu	03	Cappuccino	3%	9	35	55	97%
LS006	3% Malibu	04	Honeywheat	3%	9	44	47	97%
LS011	3% Newport	01	Powder	3%	11	65	24	97%
LS011	3% Newport	02	Bone	3%	16	57	27	97%
LS011	3% Newport	03	Nickel	3%	12	47	41	97%
LS011	3% Newport	04	Bronze	3%	4	4	92	97%
LS011	3% Newport	05	Onyx	3%	4	3	93	97%
LS011	3% Newport	06	Carbon	3%	6	9	85	97%
LS027	3% Providence	02	Amore Pink	3%	N/A	N/A	N/A	97%
LS027	3% Providence	03	Silver	3%	N/A	N/A	N/A	97%
LS027	3% Providence	04	Soft Sky	3%	N/A	N/A	N/A	97%
LS027	3% Providence	05	Fair Haven	3%	N/A	N/A	N/A	97%
LS027	3% Providence	06	Seabrook	3%	N/A	N/A	N/A	97%
LS050	3% Revival	01	Static Noise	3%	N/A	N/A	N/A	97%

SOLAR OPTICAL CHART

Collection Code	Collection Name	Color	Color Name	Openness	Transmission*	Reflection*	Absorption*	UV Rating
LS050	3% Revival	02	Paradise	3%	N/A	N/A	N/A	97%
LS050	3% Revival	03	Enchantment	3%	N/A	N/A	N/A	97%
LS028	3% Shangrila	02	Sand	3%	N/A	N/A	N/A	97%
LS028	3% Shangrila	03	Sea Grass	3%	N/A	N/A	N/A	97%
LS048	3% Solapur	01	Powder	3%	30	63	8	95%
LS048	3% Solapur	03	Onyx	3%	3	3	93	97%
LS048	3% Solapur	04	Bronze	3%	3	6	91	97%
LS048	3% Solapur	05	Bone	3%	15	70	15	97%
LS048	3% Solapur	06	Nickel	3%	8	51	40	97%
LS045	3% Stonewash	01	Fossil	3%	N/A	N/A	N/A	97%
LS045	3% Stonewash	02	Denim	3%	N/A	N/A	N/A	97%
LS045	3% Stonewash	03	Ocean	3%	N/A	N/A	N/A	97%
LS009	5% Acadia	01	Powder	5%	25	62	13	95%
LS009	5% Acadia	02	Bone	5%	24	52	24	95%
LS009	5% Acadia	03	Nickel	5%	16	38	46	95%
LS009	5% Acadia	04	Onyx	5%	6	5	89	95%
LS009	5% Acadia	05	Carbon	5%	7	16	77	95%
LS015	5% Catalina	01	Powder	5%	25	62	13	95%
LS015	5% Catalina	02	Bone	5%	23	51	26	95%
LS015	5% Catalina	03	Nickel	5%	18	44	38	95%
LS015	5% Catalina	04	Bronze	5%	4	5	91	95%
LS015	5% Catalina	05	Onyx	5%	5	5	90	95%
LS015	5% Catalina	06	Carbon	5%	6	12	82	95%
LS005	5% Key West	01	Cocoa	5%	6	12	82	95%
LS005	5% Key West	02	Doe	5%	12	37	51	95%
LS005	5% Key West	03	Mink	5%	9	24	68	95%
LS005	5% Key West	04	Oatmeal	5%	19	65	16	95%
LS005	5% Key West	05	Burlap	5%	16	45	39	95%
LS005	5% Key West	06	Barley	5%	19	56	24	95%
LS005	5% Key West	07	Iron Ore	5%	5	11	84	95%
LS012	5% Newport	01	Powder	5%	15	63	22	95%
LS012	5% Newport	02	Bone	5%	18	56	26	95%
LS012	5% Newport	03	Nickel	5%	14	46	40	95%
LS012	5% Newport	04	Bronze	5%	6	4	90	95%
LS012	5% Newport	05	Onyx	5%	6	4	90	95%
LS012	5% Newport	06	Carbon	5%	8	9	83	95%
LS047	5% Solapur	01	Powder	5%	32	61	8	95%
LS047	5% Solapur	03	Onyx	5%	6	3	91	95%
LS047	5% Solapur	04	Bronze	5%	7	6	87	95%
LS047	5% Solapur	05	Bone	5%	18	66	15	95%
LS047	5% Solapur	06	Nickel	5%	11	45	44	95%
LS007	5% Sonoma	01	Moss	5%	N/A	N/A	N/A	95%
LS007	5% Sonoma	02	Ocean	5%	N/A	N/A	N/A	95%
LS007	5% Sonoma	03	Biscuit	5%	N/A	N/A	N/A	95%
LS007	5% Sonoma	04	Sea Glass	5%	N/A	N/A	N/A	95%
LS007	5% Sonoma	05	Blush	5%	N/A	N/A	N/A	95%
LS007	5% Sonoma	06	Rosemary	5%	10	31	59	95%
LS007	5% Sonoma	07	Java	5%	8	15	77	95%

SOLAR OPTICAL CHART


Collection Code	Collection Name	Color	Color Name	Openness	Transmission*	Reflection*	Absorption*	UV Rating
LS007	5% Sonoma	08	Pebble	5%	9	33	58	95%
LS007	5% Sonoma	09	Merlot	5%	N/A	N/A	N/A	95%
LS007	5% Sonoma	10	Toast	5%	12	42	46	95%
LS046	10% Solapur	01	Powder	10%	34	59	7	90%
LS046	10% Solapur	03	Onyx	10%	12	3	85	90%
LS046	10% Solapur	04	Bronze	10%	12	6	82	90%
LS046	10% Solapur	05	Bone	10%	22	66	12	90%
LS046	10% Solapur	06	Nickel	10%	N/A	N/A	N/A	90%

*See **SOLAR OPTICAL INFORMATION** section for detail.

PARTS AND COMPONENTS


Fabric Valance

Isometric Item #	Part #	Description
1	Fabric PN	Fabric
2	1003377	Valance - ULTRA RS VALANCE 3.5 WHT 192 2
3	1003297	Return - VAL RND CORNER 3.5X1001
4	1100071	Valance Corner (FOR RETURN OPTION ONLY) - RND 3.5 WHT-CLR CAP
5	LBV20	Instl. brackets - WALL BRACKETS 2IN - ULTRA RS V
6	KIT-RS-001R	Instl. screws - KIT SCREWS 02-70-9021 4PKI



PARTS AND COMPONENTS

Cordless Lift PerfectPlacement™ Open Roll



1. Mounting Brackets

KIT-RS-012R KIT CORDLESS BKT 2PK
KIT-RS-013R KIT CORDLESS BKT 3PK

2. Mounting Bar

1049285 - White
1049287 - Vanilla
1049286 - Anodized
1049288 - Bronze
1049284 - Black

3. Filler Block

1050873 - Clear Opaque

4. Mounting Bar Bracket

1049569 - 40mm White
1049570 - 40mm Vanilla
1049571 - 40mm Zinc
1049572 - 40mm Bronze
1049573 - 40mm Black
1049574 - 55mm White
1049575 - 55mm Vanilla
1049576 - 55mm Zinc
1049577 - 55mm Bronze
1049578 - 55mm Black

5. Bracket Cover

1044231 - 40mm White
1044232 - 40mm Vanilla
1044233 - 40mm Gray
1044235 - 40mm Bronze
1044234 - 40mm Black
1044236 - 55mm White
1044237 - 55mm Vanilla
1044238 - 55mm Gray
1044240 - 55mm Bronze
1044239 - 55mm Black

6. Tube

11181712-010101

7. Springs

1052393 Spring A
1052394 Spring B
1052395 Spring C
1052396 Spring D
1052397 Spring E
1052398 Spring F
1052399 Spring G
1052400 Spring H
1052401 Spring I
1052402 Spring J
1052403 Spring K
1052404 Spring L

Not shown:

1052405 Internal head lock
1052406 Internal head spring

7a. Brake (if applicable)

1051055

8. Omni Bottom Rail

1031843 - Matte Silver
1031844 - Matte White
1031845 - Matte Black
1031846 - Matte Vanilla
1031847 - Matte Bronze

9. Spline

RC445085

10. Idler

1053024

11. Handle for Omni Bottomrail

1042827 - Clear


12. Endcap for Omni Bottomrail

1045036 - White
1045037 - Vanilla
1045038 - Gray
1045039 - Black
1045040 - Bronze

13. Roller Fabric

PARTS AND COMPONENTS

Cordless Lift PerfectPlacement™ Cassette



1. Omni Bottom Rail

1031843 - Silver
1031844 - White
1031845 - Black
1031846 - Vanilla
1031847 - Bronze

2. Omni Bottom Rail End Cap

1045036 - White
1045037 - Vanilla
1045038 - Gray
1045039 - Black
1045040 - Bronze

3. Idler

1053024

4. Roller Fabric

5. Springs

1052393 Spring A
1052394 Spring B
1052395 Spring C
1052396 Spring D
1052397 Spring E
1052398 Spring F
1052399 Spring G
1052400 Spring H
1052401 Spring I
1052402 Spring J
1052403 Spring K
1052404 Spring L

Not Shown:

1052405 Internal Head Lock
1052406 Internal Head Spring

5a. Brake (if applicable)

1051055

6. Tube

11181712-010101 - Tube 1.5"

7. Bracket

CRUSLB660

8. Installation Bracket

SB20-0202-025100 Cassette 100 Mounting
Bracket Zinc
(KIT-RS-008R 2PK; KIT-RS-009R 3PK)
V2BKT Large Cassette Mounting Bracket
(KIT-RS-006R 2PK; KIT-RS-007R 3PK)

9. Large Curved Cassette

1033801 - Silver
1033800 - Black
1033802 - Bronze
1033799 - White
1033803 - Vanilla

Medium Curved Cassette

1033798 - White
1033795 - Black
1033796 - Bronze
1033797 - Vanilla
1033794 - Silver

10. Large Curved End Cap

1033814 - Black
1033815 - White
1033816 - Bronze
1033817 - Vanilla
1033818 - Gray

Medium Curved End Cap


1033813 - White
1033812 - Vanilla
1033811 - Bronze
1033810 - Black
1033809 - Gray

11. Handle

1042827 - Handle; Omni w/Tab

PARTS AND COMPONENTS

Continuous Loop Control




PARTS AND COMPONENTS

Continuous Loop Control

- | | | |
|--|---|--|
| <p>1. End Plug For 1.5" Tube
3202504661 - White
3202504765 - Black
3202504048 - Gray</p> <p>For 2" Tube, Large Shades
SLPEHD53W - White
SLPEHD53BK - Black</p> <p>2. Large Cassette
1033801 - Silver
1033800 - Black
1033802 - Bronze
1033799 - White
1033803 - Vanilla</p> <p>Medium Cassette
1033798 - White
1033795 - Black
1033796 - Bronze
1033797 - Vanilla
1033794 - Silver</p> <p>3. Clutch
1043975 - White
1043976 - Black
SL20H53W - White
SL20H53BK - Black
SL30H53W - White
SL30H53BK - Black</p> <p>4. Large End Cap
1033814 - Black
1033815 - White
1033816 - Bronze
1033817 - Vanilla
1033818 - Gray</p> <p>Medium End Cap
1033813 - White
1033812 - Vanilla
1033811 - Bronze
1033810 - Black
1033809 - Gray</p> <p>5. Tensioner Bracket Mounting Kit
1045675</p> <p>6. Tensioner
1042235 - Black
1042236 - Bronze
1042237 - Stainless Steel
1044053 - Rich Cream
1044054 - White Tiara</p> <p>7. Heat Sealed Bottomrail
2361-01-000</p> <p>8. Plastic Chain White
1045995 - 24"
1045996 - 30"
1045997 - 36"
1045998 - 42"
1045999 - 48"
1046000 - 54"
1046001 - 60"
1046002 - 66"</p> | <p>1046003 - 72"
1046005 - 84"
1046007 - 96"</p> <p>Grey
1046008 - 24"
1046009 - 30"
1046010 - 36"
1046011 - 42"
1046012 - 48"
1046013 - 54"
1046014 - 60"
1046015 - 66"
1046016 - 72"
1046018 - 84"
1046020 - 96"</p> <p>Black
1046021 - 24"
1046022 - 30"
1046023 - 36"
1046024 - 42"
1046025 - 48"
1046026 - 54"
1046027 - 60"
1046028 - 66"
1046029 - 72"
1046031 - 84"
1046033 - 96"</p> <p>Vanilla
1046034 - 24"
1046035 - 30"
1046036 - 36"
1046037 - 42"
1046038 - 48"
1046039 - 54"
1046040 - 60"
1046041 - 66"
1046042 - 72"
1046044 - 84"
1046046 - 96"</p> <p>Brown
1046047 - 24"
1046049 - 36"
1046050 - 42"
1046051 - 48"
1046052 - 54"
1046053 - 60"
1046054 - 66"
1046055 - 72"
1046057 - 84"
1046059 - 96"</p> <p>Metal Chain
1034758 - Gun Metal
RC133307 - Stainless Steel
1044497 - Oil Rubbed Bronze</p> <p>9. Universal Brackets 40mm
1021242 - 40mm White
1021244 - 40mm Black</p> <p>10. Universal Brackets 55mm
1021245 - 55mm White
1021247 - 55mm Black</p> | <p>11. Universal Brackets 75mm
3200903661 - 75mm White
3200903048 - 75mm Black</p> <p>12. Dual Mounting Brackets
XLB61 - White
XLB65 - Black</p> <p>13. Bracket Covers
40mm Cover
1044231 - White
1044232 - Vanilla
1044233 - Gray
1044234 - Black
1044235 - Bronze</p> <p>55mm Cover
1044236 - White
1044237 - Vanilla
1044238 - Gray
1044239 - Black
1044240 - Bronze</p> <p>75mm Cover
1044241 - White
1044242 - Vanilla
1044243 - Gray
1044244 - Black
1044245 - Bronze</p> <p>14. Standard Bracket Large Curved Cassette
KIT-RS-006R - 2 pack
KIT-RS-007R - 3 pack</p> <p>15. Standard Bracket Medium Curved Cassette
KIT-RS-008R - 2 pack
KIT-RS-009R - 3 pack</p> |
|--|---|--|

PARTS AND COMPONENTS

InMotion™ Wand



PARTS AND COMPONENTS

InMotion™ Wand

- 1. Bracket**
 - 1021242 - 40mm White
 - 1021244 - 40mm Black
 - 1021245 - 55mm White
 - 1021247 - 55mm Black
 - 3200903661 - 75mm White
 - 3200903048 - 75mm Black
- 2. Hanger**
 - 1034422 - White
 - 1034423 - Black
- 3. InMotion™ Wand**
 - 1FT Wand**
 - 1034303 - White
 - 1034408 - Vanilla
 - 1034413 - Gray
 - 1034403 - Bronze
 - 1034308 - Black
 - 2FT Wand**
 - 1034304 - White
 - 1034409 - Vanilla
 - 1034414 - Gray
 - 1034404 - Bronze
 - 1034309 - Black
 - 3FT Wand**
 - 1034305 - White
 - 1034410 - Vanilla
 - 1034415 - Gray
 - 1034405 - Bronze
 - 1034400 - Black
 - 4FT Wand**
 - 1034306 - White
 - 1034411 - Vanilla
 - 1034416 - Gray
 - 1034406 - Bronze
 - 1034401 - Black
 - 5FT Wand**
 - 1034307 - White
 - 1034412 - Vanilla
 - 1034417 - Gray
 - 1034407 - Bronze
 - 1034402 - Black
 - 6FT Wand**
 - 1040190 - White
 - 1040191 - Vanilla
 - 1040192 - Gray
 - 1040193 - Bronze
 - 1040194 - Black
- 4. InMotion™ Wand Charger**
 - 1027720
- 5. Omni Bottomrail Endcap**
 - 1045036 - White
 - 1045037 - Vanilla
 - 1045038 - Gray
 - 1045039 - Black
 - 1045040 - Bronze
- 6. Omni Curved Bottomrail**
 - 1031843 - Silver
 - 1031844 - White
 - 1031845 - Black
 - 1031846 - Vanilla
 - 1031847 - Bronze
- 7. Fabric**
- 8. Open Roll Bracket Covers**
 - 40mm Cover**
 - 1044231 - White
 - 1044232 - Vanilla
 - 1044233 - Gray
 - 1044234 - Black
 - 1044235 - Bronze
 - 55mm Cover**
 - 1044236 - White
 - 1044237 - Vanilla
 - 1044238 - Gray
 - 1044239 - Black
 - 1044240 - Bronze
 - 75mm Cover**
 - 1044241 - White
 - 1044242 - Vanilla
 - 1044243 - Gray
 - 1044244 - Black
 - 1044245 - Bronze
- 9. Crown/Drive**
 - 1034420 25mm for 1.5" Tube
- 10. End Plug**
 - 3202504765 Gray
 - 3202504661 White
 - 3202504048 Black
- 11. Motor**
 - 1034419 - 1.0Nm
 - 1045483 - 2.0Nm
- 12. Tube**
 - 11181712-010101 Tube 1.5"