

AUTOMATION CONFIGURATION SPECIFICATIONS

NOTE: Use metal tape measure for all measurements. Measures to 1/8 inch.

AUTOMATION BU & TDBU LI-ION (INTERNAL BATTERY)

- Li-Ion= Features Internal Battery
- Features the same headrail and bottomrail as Cordless Lift. Fabric wrapped rails are available for a surcharge. Color-coordinated rails are available at no additional charge. Must be specified when ordering.



	SIZE STANDARDS			
	Bottom-Up		Top-Down/Bottom-Up	
	Cellular Fabrics	2w Hybrid Pleat	Right Side Control	Left Side Control
Minimum NET Width*	18-1/8'	18-1/8'	30'	35'
Maximum Width	120'	120'	120'	120'
Minimum Height	12'	12'	18'	18'
Maximum Height	108'	108'	108'	108'

NOTES:

1. Max height varies by width and fabric type. Refer to chart automation maximum heights chart

2. End Mount not available

The minimum inside mount width is 19w for single, large and double when ordered with hold-down brackets

AUTOMATION MAXIMUM HEIGHTS Bottom-Up

CODE	SHADE NET WIDTH TO:	18" – 72" *	84"	96"	108"	120"
					65 Sq Ft Max - Over 96"	
IBLS	Softstyle Light Filtering - Large Single Cell	108"	108"	108"	87"	78"
		50 Sq Ft Max - Up to 96"			45 Sq Ft Max - Over 96"	
IBLD	Softstyle Light Filtering - Double Cell	100"	85"	75"	60"	54"
		80 Sq Ft Max - Over 96"				
IBLB	Softstyle Blackout - Large Single Cell	108"	108"	108"	106"	96"
		55 Sq Ft Max - Up to 96"			45 Sq Ft Max - Over 96"	
IBBD	SoftStyle 1/2" Double Cell Double Cell Blackout	108"	94"	82"	60"	54"

FINISHED DIMENSIONS MOUNTING REQUIREMENTS

Adjustments are taken from ordered dimensions.

Use a metal tape measure for all measurements.

Inside (IB) Mounts	Cellular	2"Hybrid Pleat
Headrail unit	- 1/4'	- 1/4'
Shade height	ordered height	ordered height
Fabric width	- 3/8'	- 3/8'
Outside (OB) Mount		
Headrail unit	ordered width	ordered width
Shade height	ordered height	ordered height
Fabric width	- 1/8'	- 1/8'

NOTE: Measurements may vary \pm 1/8'

Inside (IB) Mount	Cellular Fabrics & Hybrid Pleat
Minimum mounting depth	3/4'
Minimum mounting depth, flush mount:	2-1/8'
Outside (OB) Mount	
Minimum flat vertical surface	1-1/2'

Extension Brackets required for Battery - Mounted to the back of the Headrail

Extension Brackets required for Battery - Mounted to the back of the Headrail