
RECTANGULAR CONFIGURATION SPECIFICATIONS

NOTE: Use metal tape measure for all measurements. Measures to 1/8 inch.

CORDLESS LIFT SYSTEM



Uses steel snap-in brackets. Cordless easily lifts and lowers using the bottomrail handle. No lift cord is necessary.

All Cordless shades can be ordered with the fabric covered headrail and bottomrail for a surcharge, or with the color coordinated non-wrapped rails at no additional charge. Must be specified when order is placed.order is placed.

Cordless cellular shades come with a color-coordinated textured handle pre-inserted, a clear textured handle or clear plastic insert are optional.

Shades over 42" will have two handles. Single handle available, must be selected during order entry. Cut-Outs are not available.

CORDLESS LIFT - SIZE STANDARDS				
	Cellular			2" Hybrid Pleat
	3/4" Light Filtering & Blackout Fabrics	Double cell Light Filtering Fabrics	Double cell Blackout Fabrics	Light Filtering & Blackout
Min. Width (net)	14"	16"	16"	16"
Max. Width	120"	120"	96"	120"
Max. Width - End Mount	48"	48"	48"	42"
Min. Height	12"	12"	12"	12"
Max. Height	84"	84"	84"	84"
Max Area (sq. ft.)	60	60	56	60

Note: Cut-outs are not available on Cordless Lift shades.

CORDLESS LIFT TWO-ON-ONE - SIZE STANDARDS				
	Cellular			2" Hybrid Pleat
	3/4" Light Filtering & Blackout Fabrics	Double cell Light Filtering Fabrics	Double cell Blackout Fabrics	LightFiltering &Blackout
Min Width (per panel)	14"	16"	16"	16"
Min Width (overall)	28"	32"	32"	32"
Max Width (per panel)	100"	100"	96"	100"
Max Width (overall)	120"	120"	120"	120"
Min Height	12"	12"	12"	12"
Max Height	84"	84"	84"	84"
Max Area (per panel) (Sq/Ft)	60	56	56	60

^{*} Two-On-One Headrail is not available in Top-Down/Bottom-Up or Trilight Note: End mount not available. Not available with Hold Down Brackets Note: Cut-outs are not available on Cordless Lift shades

CORDLESS LIFT TOP-DOWN/BOTTOM-UP - SIZE STANDARDS				
	Cellular			2" Hybrid Pleat
	All Light Filtering Fabrics	Subdue Blackout (S61)	All other Blackou Fabrics	Light Filtering & Blackout
Min. Width (net)	16"	16"	16"	16"
Max. Width	96"	84"	96"	120"
Max. Width – End Mount	48"	48"	48"	42"
Min. Height	12"	12"	12"	12"
Max. Height	84"	84"	84"	84"
Max Area (sq. ft.)	56	49	56	60

Note: Cut-outs are not available on Cordless Lift shades.

CORDLESS LIFT THREE-ON-ONE – SIZE STANDARDS				
	Cellular			2" Hybrid Pleat
	3/4"LightFiltering &Blackout Fabrics	Double cell Light Filtering Fabrics	Double cell Blackout Fabrics	LightFilering &Blackout
Min Width (per panel)	14"	16"	16"	16"
Min Width (overall)	42"	48"	48"	48"
Max Width (per panel)	100"	100"	96"	120"
Max Width (overall)	174"	174"	174"	174"
Min Height	12"	12"	12"	12"
Max Height	84"	84"	84"	84"
Max Area (per panel) (Sq/Ft)	60	60	56	60

^{*} Three-On-One Headrail is not available in Top-Down/Bottom-Up or Trilight Note: End mount not available. Not available with Hold Down Brackets Note: Cut-outs are not available on Cordless Lift shades.

FINISHED DIMENSIONS MOUNTING REQUIREMENTS

Adjustments are taken from ordered dimensions.

SoftStyle 2" Hybrid Pleat		
Inside (IB) Mounts		
Headrail unit (includes end caps)	- 1/4"	- 1/4"
Shade height	ordered height	ordered height
Fabric width	- 3/8"	- 3/8"
End (EB) Mounts		
Headrail unit (includes end caps)	- 1/2"	- 1/2"
Shade height	ordered height	ordered height
Fabric width	- 5/8"	- 5/8"
Outside (OB) Mount		
Headrail unit (includes end caps)	ordered width	ordered width
Shade height	ordered height	ordered height
Fabric width	- 1/8"	- 1/8"
2-on-1 & 3-on-1 Headrail		
Gap between panels – 1/4"		- 1/4"

NOTE: Measurements may vary +/- 1/8".

Use a metal tape measure for all measurements.

SoftStyle 2" Hybrid Pleat

Inside (IB) & End (EB) Mounts			
Minimum mounting depth	3/4"	3/4"	
Minimum mounting depth, flush mount:	2-1/8"	2-1/8"	
Outside (OB) Mount			
Minimum flat vertical surface		1-1/2" 1-1/2"	

NOTE: Inside mount with hold down brackets deductions:

Headrail -1/2" Fabric -5/8" Bottomrail -1/2"